TANKS

DOUBLE ADSORPTION SACK & FRAME

Sacks enable retention of solids and oil residue, whilst allowing effluent to filter and drain

Heavy duty sacks, ideal for onsite waste. Specially designed to allow the fast flow of water whilst retaining solids and adsorbing contaminants. Ideal for washing concrete equipment off into and other onsite waste disposal.

NO DOWNTIME The beauty of a double system is that the system can continue to be used when changing one of the sacks or waiting for a sack to drain. Allowing the sacks to drain for longer increases their usage. Additionally, sump capacity is also increased.

No power is required

Simple to set up, empty and operate

Solids are retained in sack

Dims (mm) approx.	2220 (L) 1440 (W) 1100 (H)
Weight approx.	Unladen: 600kg (open)
	900kg (enclosed)
	Laden: 2600kg / 2900kg
Power Required	Not Required
Consumables	Adsorption Sacks
	,
Capacity approx.	500ltrs (open)
	2000ltrs (enclosed)
Torrigore at all annual at another BOA	

Transport charged at cost – POA

50% deposit required at point of order for purchases

Remaining balance required prior to delivery

AVAILABLE FOR HIRE OR PURCHASE

For further information contact KELLY TANKS on 01889 508944 or email info@kellytanks.co.uk





